




PHOTOELECTRIC SENSOR



DIFFUSE

LTR-D04MA-NS




12 mm


- ✓ Ø4 miniature housing
- ✓ Focused RED light source
- ✓ IO-Link
- ✓ Calibrated range
- ✓ Embeddable
- ✓ Immunity to mutual interference



Cable type



Pigtail type



Connector type

OPTICAL DATA		INTERFACE	
Sensing range typ. max.	0...12 mm ¹	Sensitivity adjustment	none
Operating range	0...10 mm ¹	Indicator LED, green	Excess gain
Light source	LED, red 630 nm	Indicator LED, yellow	Sensing state
Light spot size (distance)	Ø 5 mm (10 mm)	IO-Link	✓

¹Object with 90% reflectance (standard white paper)


ELECTRICAL DATA		MECHANICAL DATA	
Supply voltage range (U _b)	10...30 VDC	Enclosure rating	IP67
Residual ripple	≤ 10% V _{pp}	Ambient temperature operation	-25...+65°C
Output current	≤ 100 mA	Shock and vibration	IEC 60947-5-2
Signal PNP high/low	≤ (U _b -2.0 V)/approx. 0 V	Weight (cable/connector/pigtail)	30 g / 4 g / 12 g
Signal NPN high/low	Approx. U _b /≤ 2.0 V	Housing material	V2A stainless steel
Power consumption (no load)	≤ 12 mA	Optics material	PBT / PMMA
Response time ¹	≤ 500 µs (normal)/≤ 1 ms/≤ 200 µs	Cable type	PUR, 2 m, 3-wire
Switching frequency ¹	≤ 1 kHz (normal)/≤ 500 Hz/≤ 2.5 kHz	Pigtail type	PUR, L=0.3 m, M8 3-pin
Short circuit protection	✓	Connector type	M8 3-pin
Voltage reversal protection	✓		

¹By default, "Normal" mode. "Fine" and "Fast" modes selectable via IO-Link.

SENSING RANGE

EXCESS GAIN

Target	Operating range	Sensing range max.
90%	0...10 mm	0...12 mm
18%	0.5...5 mm	0.3...6.5 mm
6%	0.8...2 mm	0.6...2.3 mm





IO-LINK FUNCTIONALITIES

IO-Link version	1.0
SIO mode	Supported
Process data	Detection state & stability alarm
Baudrate	COM2 (38.4 kBaud)
Special functions	Output configuration, output timing, sensor mode, detection counter, event flags, maximum and actual sensor temperature

IO-Link specifications and IODD files may be downloaded from www.contrinex.com (Download section)

WIRING DIAGRAM

PIN ASSIGNMENT



AVAILABLE TYPES

Part number	Part reference	Polarity	Connection	Output (A1)
620-600-362	LTR-D04MA-NSK-403	PNP	PUR, 2 m, 3-wire	Light-on/IO-Link
620-600-373	LTR-D04MA-NSV-403	PNP	PUR, L=0.3 m, M8 3-pin	Light-on/IO-Link
620-600-393	LTR-D04MA-NSS-403	PNP	M8 3-pin	Light-on/IO-Link
620-600-359	LTR-D04MA-NSK-301	NPN	PUR, 2 m, 3-wire	Light-on
620-600-370	LTR-D04MA-NSV-301	NPN	PUR, L=0.3 m, M8 3-pin	Light-on
620-600-390	LTR-D04MA-NSS-301	NPN	M8 3-pin	Light-on

Note: additional suffix can appear to indicate a revision version or a special version.

Operators of the products we supply are responsible for compliance with measures for the protection of persons. The use of our equipment in applications where the safety of persons might be at risk is only authorized if the operator observes and implements separate, appropriate and necessary measures for the protection of persons and machines. Terms of delivery and rights to change design reserved.