


STANDARD CONFIGURATIONS UNLESS OTHERWISE NOTED		
CONN. TYPE	EXTERIOR	INTERIOR
ALL D-SUBS	FEMALE	MALE
RJ45	CAT 6 JACK	CAT 6 JACK

MOUNTING KIT ORDERED
SEPARATELY CONTAINS
M4x0.7 SS SCREW, NYLON WASHER,
SPLIT LOCKWASHER AND M4 NUT
P/N: D-PIC-MT



HOUSING MATERIALS		NEMA/UL EN 60529:		4, 12 IP65	
BODY:	EPOXY COATED DIE CAST ALUMINUM	PANEL THICKNESS:		5.0mm max	
		MOUNTING SCREW TORQUE:		0.8N-m	
GASKET:	THERMOPLASTIC ELASTOMER	TERMINAL BLOCK TORQUE:		0.5N-m	
HANDLE:	POLYAMIDE	INCOMING POWER WIRE SIZE:		0.25 - 2.5 sq mm / 24-12AWG	
LEVERS:	STAINLESS STEEL	WIRE STRIP LENGTH:		7 - 8 mm	
N WASHER, M4 NUT		UNLESS OTHERWISE SPECIFIED:		MENCOM CORPORATION TITLE: GF; DB9; 2RJ45; 32	
		DIMENSIONS ARE IN INCHES AND [MM]			
		DRAWN BY	DCG		
		DRAWN DATE	11/21/2018		
		CHECKED BY	GO		
		CHECK DATE	11/26/2018	SIZE DWG. NO. REV B GF-DB9-2RJ45-32 D	
COMMENTS:					
		MATERIAL		SCALE: 2:3 WEIGHT: SHEET 1 OF 1	
		FINISH			
		DO NOT SCALE DRAWING			